



I.Fw

NEIFELD IP LAW, P.C.
2001 Jefferson Davis Highway
Suite 1001, Crystal Plaza 1
Arlington, VA 22202

Tel: 703-415-0012
Fax: 703-415-0013
Email: rneifeld@Neifeld.com
Web: www.Neifeld.com

TRANSMITTAL LETTER

ASSISTANT COMMISSIONER FOR PATENTS
WASHINGTON, D.C. 20231

RE: Attorney Docket No.: EFFE0010UEP-US
Application Serial No.: 10/815,759
Filed: 04/02/04
Title: Combining First and Second Image Data of an Object
Inventor: SAKAS

SIR:

Attached hereto for filing are the following papers:

37 CFR 1.55(a)(1) Claim for Foreign Priority (2 Pages)
37 CFR 1.55(a)(2) Filing of Certified Copy of a Priority Document (2 Pages)

Our check in the amount of 0.00 is attached covering the required fees.

The Commissioner is hereby authorized to charge any fees which may be required, or credit any overpayment, to Deposit Account Number 50-2106. A duplicate copy of this sheet is enclosed.

31518

PATENT TRADEMARK OFFICE

6/2/2004

Date


Richard A. Neifeld, Ph.D.
Registration No. 35,299
Attorney of Record

Printed: June 2, 2004 (12:10pm)
Y:\Clients\Effert, Bressel und
Kollegen\EFFE0010\EFFE0010UEP-US\Drafts\Transmittal_040520.wpd



THIS PAGE BLANK (USPTO)

NEIFELD DOCKET NO. EFFE0010UEP-US



IN THE UNITED STATES PATENT & TRADEMARK OFFICE

IN RE APPLICATION OF: SAKAS

CONFIRMATION NO: UNKNOWN

SERIAL NO: 10/815,759

FILED: 04/02/04

EXAMINER: UNKNOWN

GROUP ART UNIT: UNKNOWN

FOR: COMBINING FIRST AND SECOND IMAGE DATA OF AN OBJECT

ASSISTANT COMMISSIONER FOR PATENTS

POB 1450 Alexandria VA 22313-1450

37 CFR 1.55(a)(1) CLAIM FOR FOREIGN PRIORITY

Remarks/Arguments begin on page 2 of this paper:



THIS PAGE BLANK (USPTO)

REMARKS

This application claims the benefit of the filing date of prior filed application(s) identified below:

European Application EP 03008448.7, filed April 11, 2003.


31518
PATENT TRADEMARK OFFICE

Neifeld IP Law, PC
2001 Jefferson Davis Highway
Suite 1001
Arlington, VA 22202

6/2/2004

Date:

Respectfully Submitted,



Richard A. Neifeld, Ph.D.
Registration No. 35,299
Attorney of Record

Tel: 703-415-0012
Fax: 703-415-0013
Email: rneifeld@Neifeld.com

Printed: June 2, 2004 (4:20pm)

Y:\Info\FirmForms\USProsecutionForms\37CFR155a1_ClaimforForeignPriority.wpd

THIS PAGE BLANK (USPTO)



**Europäisches
Patentamt**

**European
Patent Office**

**Office européen
des brevets**

Bescheinigung

Certificate

Attestation

Die angehefteten Unterlagen stimmen mit der ursprünglich eingereichten Fassung der auf dem nächsten Blatt bezeichneten europäischen Patentanmeldung überein.

The attached documents are exact copies of the European patent application described on the following page, as originally filed.

Les documents fixés à cette attestation sont conformes à la version initialement déposée de la demande de brevet européen spécifiée à la page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

03008448.7

Der Präsident des Europäischen Patentamts;
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets
p.o.

R C van Dijk

THIS PAGE BLANK (USPTO)



Anmeldung Nr:
Application no.: 03008448.7
Demande no:

Anmeldetag:
Date of filing: 11.04.03
Date de dépôt:

Anmelder/Applicant(s)/Demandeur(s):

MedCom Gesellschaft
für medizinische Bildverarbeitung mbH
Rundeturmstrasse 12
64283 Darmstadt
ALLEMAGNE
Esaote S.p.A.
Via Ruffino Aliora 32
15033 Casale Monferrato (AL)
ITALIE

Bezeichnung der Erfindung/Title of the invention/Titre de l'invention:
(Falls die Bezeichnung der Erfindung nicht angegeben ist, siehe Beschreibung.
If no title is shown please refer to the description.
Si aucun titre n'est indiqué se referer à la description.)

Combining first and second image data of an object

In Anspruch genommene Priorität(en) / Priority(ies) claimed /Priorité(s)
revendiquée(s)
Staat/Tag/Aktenzeichen/State/Date/File no./Pays/Date/Numéro de dépôt:

Internationale Patentklassifikation/International Patent Classification/
Classification internationale des brevets:

G06T/

Am Anmeldetag benannte Vertragstaaten/Contracting states designated at date of
filing/Etats contractants désignées lors du dépôt:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LU MC NL
PT SE SI SK TR LI RO

THIS PAGE BLANK (USPTO)

Applicants:

MedCom Gesellschaft für medizinische Bildverarbeitung mbH

Rundeturmstrasse 12, D-64283 Darmstadt, GERMANY and

Esaote S.p.A., via Ruffino Aliora, 32

15033 Casale Monferrato (AL), ITALY

5

Combining First and Second Image Data of an Object

10

Description

The invention relates to an apparatus and a method for/of combining first and second image data of an object. An ultrasound (US) detector repeatedly generates the first image data of the object and the second image data of the object are generated separately. In the apparatus, means for storing and/or receiving the second image data of the object (such as an image data storage and/or an interface) are provided. For example, the second image data may have been recorded earlier by a computer tomography (CT), a magnetic resonance (MR), a positron emission tomography (PET), an X-ray and/or a three-dimensional (3D) US imaging device. In particular, any 3D image information can be used as the second image data. A combination device combines the first and second image data of the object. The combined image data may be displayed in separate areas of a screen and/or may be superimposed on a screen. More particularly, the invention may be applied in the field of stereographic diagnosis concerning human or animal bodies, but also concerning material research and/or material examination.

Ultrasound detectors are comparatively easy to handle and are able to deliver image information quasi-continuously and, approximately, in real-time. However, in many applications, other imaging technologies (such as the ones mentioned above) provide better results. Therefore, it has been proposed earlier to combine image information of better quality, which has been recorded earlier, with real-time ultrasound image information.

30

MEDPT03027

2

11.04.03

In the scientific publication of Pagoulatos et al.: "Interactive 3-D Registration of Ultrasound and Magnetic Resonance Images Based on a Magnetic Position Sensor", published in IEEE TRANSACTIONS ON INFORMATION TECHNOLOGY IN BIOMEDICINE, VOL. 3, NO. 4, December 1999, describes an apparatus of the type
5 mentioned above. It is proposed in the publication to use an MR imaging device and to register the imaging object relative to the MR imaging device. The term "register" means that the geometry of the object and the coordinate system of the MR imaging device are brought into a defined relation. The apparatus comprises a position sensor, which is firmly coupled to an ultrasound probe. Using the position sensor and due to the fact that
10 its relative position to the ultrasound probe does not vary, it is possible to track the position and the orientation of the ultrasound probe. However, it is necessary to calibrate the position sensor relative to the ultrasound probe and to register the imaging object relative to the coordinate system of the ultrasound probe. As a result, the MR imaging information and the ultrasound imaging information can be combined.

15 Using systems of the type described before, it is possible to display MR image information of the same orientation and/or scaled in the same manner as the most recent US image. In other words: it can be simulated that the MR image is recorded in real-time, provided that the image data processing is fast enough.

20 However, the various calibration and registration procedures are time-consuming and need to be performed with care in order to obtain good results. For example, the position of a set of landmarks on the surface of the object and/or anatomical markers (in case of a human or animal body) is to be detected during registration.

25 Furthermore, modern US systems enable the user to vary the penetration depth of the US image in the object and/or to change the ultrasound probe. As a consequence, the calibration of the position sensor relative to the ultrasound probe and the registration of the imaging object relative to the coordinate system of the ultrasound probe are no longer valid.

30 It is an object of the present invention to provide an apparatus and a method of the type indicated above, which allow lessening the effects of the disadvantages mentioned before, which facilitate the handling by the user and which allow using a greater variety

HEDPT03027

3

11.04.03

of features of the ultrasound system without losing time for calibration and/or registration. In particular, it is desirable to adjust the settings of the ultrasound system and/or to change the ultrasound probe and to continue with the ultrasound imaging process without interruption.

- 5 A method is provided of combining first and second image data of an object, wherein the first image data of the object are repeatedly generated by an ultrasound detector, wherein the second image data of the object are generated separately, wherein the first image data are transferred from the ultrasound detector to a combination device and wherein the combination device is adapted to combine the first and second image data of the object.
- 10 Geometry data is transferred in addition to the first image data from the ultrasound detector to the combination device, wherein the geometry data comprise information for establishing a link between the geometry of the first image data and the geometry of the second image data.

- Further, an apparatus is provided for combining first and second image data of an object,
- 15 the apparatus comprising an ultrasound detector for repeatedly generating the first image data of the object; means for storing and/or receiving the second image data of the object; a combination device which is adapted to combine the first and second image data of the object; and an image data connection from the ultrasound detector to the combination device for transferring the first image data. The ultrasound detector is
- 20 connected to the combination device by a geometry data connection, wherein the geometry data connection, the ultrasound detector and the combination device are adapted to transfer geometry data additionally to the first image data from the ultrasound detector to the combination device and wherein the geometry data comprise information for establishing a link between the geometry of the first image data and the geometry of
- 25 the second image data.

- The "link" (or, in other words, a processable relation between the first and the second image data) allows, for example, determining an overlapping region of a first image represented by the first image data and of a second image represented by the second image data. According to a preferred application, the combination device continuously
- 30 displays a first image of the object corresponding to the repeatedly generated first image

MEDPT03027

4

11.04.03

data and continuously displays a second image of the object corresponding to the second image data, wherein the orientation and/or scaling of at least a part of the object is identical in the first and in the second image. In particular, the second image data may be displayed, as if the second image data have repeatedly been recorded instead of or in addition to the first image data.

As a consequence of the fact that the geometry data are available to the combination device, the effort for re-calibrating the ultrasound detector relative to a tracking sensor (if any) and/or for re-registrating the object relative to the coordinate system of the ultrasound detector can be reduced or eliminated.

- 10 The geometry data may comprise, for example, one or more than one of the following type of information:
- a) information concerning at least one spatial dimension of an image unit of the first image data, in particular of a pixel (preferably separately for different directions of a coordinate system);
 - 15 b) information concerning an image position of at least a part of an image, which is represented by the first image data, relative to a reference point of the ultrasound detector or relative to a reference point or reference object in the ultrasound image. This information is particularly useful, if a user can adjust a zoom factor of the ultrasound image. For example, this information comprises a distance in image units (e.g. pixels). In combination with the scaling information of item a),
20 the distance may be defined in cm or another unit of length;
 - c) information concerning a detector position of the ultrasound detector relative to a position sensor for determining a location and/or an orientation of the ultrasound detector. Instead of or in addition to a position sensor, a signal source may be
25 coupled to the ultrasound probe, wherein the signal can be evaluated in order to determine the position of the probe. For example, such information may be collected once in advance and may be saved individually for each ultrasound probe, which can be connected to the ultrasound system/device. In this case, it is sufficient during operation to transfer simply an identification signal, which

MEDPT03027

5

11.04.03

enables to identify the probe that is used. The combination device can select the respective geometry information using the identification information. In a specific embodiment, the information concerning the relative position, which is transferred or saved, may be a calibration matrix;

- 5 d) information concerning an orientation of the ultrasound image relative to a reference point or a reference object of the ultrasound detector (in particular an ultrasound probe of the detector). For example, this information may comprise the orientation of at least one axis of a coordinate system of the ultrasound image; and
- 10 e) information concerning a region or an area, which is actually covered by an ultrasound image that is represented by the first image data.

Preferably, all of these types of information are transferred from the ultrasound detector to the combination device.

- 15 According to a preferred embodiment at least a part of the geometry data is repeatedly transferred to the combination device, in particular every time when the first image data are generated and/or when the first image data are transferred to the ultrasound detector. The geometry data may be transferred on request and/or without request from the combination device and/or from another part or unit (for example of a central control unit) of the apparatus.

- 20 There are further possibilities to use the additional data connection between the ultrasound detector and the combination device, or to use a further data connection. For example, a mode and/or a user setting of the ultrasound detector may be transferred from the ultrasound detector to the combination device, on request or without request of the combination device or another unit of the apparatus. E.g. a colour of the ultrasound
- 25 image to be used in displaying the ultrasound image, a repetition frequency of the ultrasound image generation (for example in order to give an indication to the user, if the frequency is too low) and/or information representing the object may be transferred.

If the ultrasound detector comprises a control unit for controlling an image data generation of the ultrasound detector, the control unit may be adapted to generate at

MEDPT03027

6

11.04.03

least a part of the geometry data. For example, the control unit can adjust a penetration depth of the ultrasound image, using a velocity value of the ultrasound waves in the object, by setting a time limit for detection of US echo signals. In this case, the control unit can calculate the penetration depth and can transfer information about the penetration depth to the combination device. Further, the width of an image recording area of an ultrasound probe may be available to the control unit for control purposes and the control unit can transfer this information to the combination device.

In a preferred embodiment of the apparatus the image data connection is adapted to directly transfer the first image data in a digital format from the ultrasound detector to the combination device. This saves time for transferring the first image data and reduces costs and effort of the apparatus. Furthermore, the ultrasound detector, the combination device and (optionally) further parts or units of an imaging system may be integrated in one and the same device. For example, several or all of the units of such a device may be connected to a data bus system for transferring data.

Generally, the image data connection and/or the geometry data connection may be realised by a data bus (e.g. USB or FireWire, IEEE 1394) and/or may be part of a data network. Preferably, the embodiment of the connection or connections shall allow displaying a first image (represented by the first image data) and a second image (represented by the second image data) approximately in real-time of the generation of the first image data, for example within less than 100 ms after the generation. Ultrasound is particularly useful in order to generate the first image data, since the generation process can be performed with high repetition frequency (quasi-continuously). The corresponding data connection and the following data processing should not delay the displaying in way, which can be noticed by the user.

In the following, examples and possible further features of the invention are described by way of reference to the accompanied drawing. The embodiment shown in the figures 1 to 3 and 5 represent the currently known best mode of the invention. However, the invention is not limited to the features described in the following description. The figures of the drawing schematically show:

MEDPT03027

7

11.04.03

Fig. 1 an arrangement 2 comprising an apparatus for combining ultrasound image data with a second type of data, e.g. CT image data;

Fig. 2 a more detailed view of the ultrasound detector shown in Fig. 1;

Fig. 3 a first example of an arrangement of components, which contribute to a processing of the ultrasound image data;

Fig. 4 a second example of an arrangement of components, which contribute to a processing of the ultrasound image data;

Fig. 5 a flow-chart of processing image data.

10 Images of an object 3 (shown in Fig. 1) are to be displayed on a screen 6. An ultrasound detector 1 generates first image data of the object 3 and transfers the first image data to a combination device 5 via an image data connection 10. The combination device 5 comprises a data storage 4, which contains second image data that have previously been generated by a separate device (not shown in Fig. 1). The combination device 5 is adapted to combine the first and second image data and to display them on a screen 6, which is connected to the combination device 5. For example, the first and second image data may be displayed separately on a split screen or may be superimposed. In any case, it is preferred that a first image, which is generated using the first image data, and a second image, which is generated using the second image data, precisely show at least partially the same area or region of the object 3 in the same orientation (angle of view) and scaling (dimensions).

The ultrasound detector 1 and the combination device 5 are connected to each other by an additional data connection 12 for transferring geometry data from the ultrasound detector 1 to the combination device 5. In particular, the geometry data connection 12 may be connected (as shown in Fig. 2) to a control unit 14 of the ultrasound detector 1.

In practice, the data connections 10, 12 may be realised by separate data connection links or by the same data connection link. For example, a "link" may comprise a connection line, a plurality of connection lines and/or a digital data bus or bus system.

MEDPT03027

8

11.04.03

An ultrasound probe 16 (Fig. 2) of the ultrasound detector 1 is firmly coupled to a position sensor 18 of a tracking system. The determination of the orientation and the location of such a position sensor and, thereby, of the ultrasound probe is known in the art (see the above-cited publication of Pagoulatos et al.). For example, magnetic and/or optical (e.g. infrared) signals may be used by the tracking system. The position sensor 18 is connected to a tracking system control unit 8 and the control unit 8 is connected to the combination device 5. During operation of the arrangement 2, the control unit 8 repeatedly or quasi-continuously transfers information concerning the position and concerning the orientation of the ultrasound probe 16 to the combination unit 5.

Alternatively, this information may be transferred from the US detector to the combination device. I.e. this information might be at least partially included in the geometry data, which are transferred.

As shown in Fig. 2, the ultrasound device 1 may, for example, comprise an ultrasound probe 16, which is connected to the ultrasound control unit 14 via a flexible cord 17 for transferring echo signals to the control unit 14. On the other hand, the control unit 14 transfers control signals to the ultrasound probe via the cord 17. Also, it is possible that at least a part of the geometry information is transferred from the ultrasound probe 16 to the control unit 14 and/or that at least a part of the geometry information generated by the control unit 14 is based on and/or derived from information, which is transferred from the ultrasound probe 16 to the control unit 14. For example, the ultrasound probe 16 may be replaced and, therefore, transfers information concerning its identity to the combination device 5. In the combination device 5, in an additional unit of the arrangement 2, and/or in the combination device 5, information concerning the relative position and/or orientation of the specific ultrasound probe 16 relative to the position sensor 18 may be saved. For example, the ultrasound probe 16 may comprise a clip for attaching the position sensor 18. Therefore, it is possible to precisely position and orientate the position sensor 18 relative to the ultrasound probe 16 and to determine as well as to save the respective geometry data in advance. After replacement of the ultrasound probe 16, the identity information and the saved geometry information can be combined. As a consequence, it is not necessary to re-calibrate the arrangement consisting of the ultrasound detector 1 and the position sensor 18.

MEDPT03027

9

11.04.03

An input unit 20 is connected to the ultrasound control unit 14, for example for inputting settings of the ultrasound detector, such as a penetration depth or range of the ultrasound image. Further, the user may change the orientation of the ultrasound image via the input unit 20.

- 5 According to a preferred embodiment of the invention, the ultrasound image data are generated from analog signals in a unit 22 of the ultrasound detector. The unit 22 may, for example, be controlled by the control unit 14 (as shown in the figure), be a part of the control unit 14 or be realised by a combination of the ultrasound probe 16 and the control unit 14. The unit 22 is connected to an A/D-converter 24, which converts the
- 10 analog image signal to a digital image signal. The A/D-converter 24 is connected to an image data processing unit 26, which is also connected to the control unit 14 or to an alternative unit of the ultrasound detector that transfers geometry information to the image data processing unit 26. Thus, the image data processing unit 26 can combine the geometry information with the image data and/or can transferred both information/data
- 15 to a further unit (not shown in figure 3). For example, the image data processing unit 26 may be identical to or part of the combination device 5. In this case, the image data processing unit 26 also combines the first and second image information and the unit 26 may be connected to a screen 6 (as shown in the figure).

- The embodiment of figure 3 is of particular advantage, if the ultrasound detector and the
- 20 combination device are integrated in one device.

In an alternative arrangement, the ultrasound detector may directly generate digital image data, without conversion from analog to digital.

- An alternative arrangement is shown in figure 4. The same reference numeral denote units or devices having the same or a corresponding function. A D/A-converter 23
- 25 converts the digital image signal received via a connection from the unit 22 or from a corresponding unit to an analog image signal, for example to a signal in standard video format. An A/D-converter 25 that may be part of the combination device (e.g. a video capture card) is connected to the unit 23. The unit 25 converts the analog signal to a digital signal, e.g. in pixel format. Then, the unit 26 processes the digital signal.

MEDPT03027

10

11.04.03

An example of processing and combining ultrasound image information is described in the following with reference to figure 5.

5 In step S1, geometry information concerning the scaling of the ultrasound image information are combined with the ultrasound image information. For example, the ultrasound image data contains information concerning the intensity of image units (e.g. pixels) before step S1, but no information concerning the dimension of the image units. The dimensional information is added by performing step S1.

10 In step S2, calibration information concerning the relative position of the ultrasound detector to the position sensor is added and/or combined with the information resulting from step S1. The calibration information may comprise as well information concerning the orientation of the ultrasound image, which may be changed by the user. As a result, it is now possible to identify the orientation and location of specific areas of the ultrasound image.

15 In step S3, the geometry information concerning the registration of the object within the coordinate system of the ultrasound system or the tracking system is added.

In step S4, the ultrasound image data resulting from step S3 can be combined with the second image data.

20 In practice, at least some of the processing operations of steps S1 to S4 may be realised by performing a polygon scanline method, which is described for example in the book "Computer Graphics. Principles and Practice." by James D. Foley, Andries VanDam, Steven K. Feiner, published by Addison-Wesley, Boston, U.S.A. The combination device 5 shown in figure 1 may perform the data processing, for example.

25 For example, it is first calculated whether an overlapping region of the respective images exists. If this is the case, the corresponding overlapping region of the second image data is read out from the data storage and is prepared for displaying (step S5). The corresponding data of the second image data are processed before displaying so that the second image, which is based on the second image data, can be displayed in the same orientation and scaling as the ultrasound image.

MEDPT03027

11

11.04.03

The procedure described before is preferred, if the ultrasound image is two-dimensional. For 3D-ultrasound image information it is as well possible, to choose the orientation (i.e. the angle of the view) of the ultrasound image to be shown, in particular to adapt the orientation according to other criteria. In any case, it is possible to adapt the scaling of
5 the ultrasound image before displaying. Instead of, or additionally to displaying, the combined first and second image information may be processed in another way. For example, they can be stored and/or evaluated in a different manner.

MEDPT03027

12

11.04.03

Patent Claims

1. An apparatus (2) for combining first and second image data of an object (3), comprising
- 5 • an ultrasound detector (1) for repeatedly generating the first image data of the object (3);
 - means (4) for storing and/or receiving the second image data of the object (3), for example image data generated by a computer tomography, a magnetic resonance, a positron emission tomography or an X-ray imaging device;
 - 10 • a combination device (5) which is adapted to combine the first and second image data of the object (3); and
 - an image data connection (10) from the ultrasound detector (1) to the combination device (5) for transferring the first image data;
- 15 characterised in that
- the ultrasound detector (1) is connected to the combination device (5) by a geometry data connection (12), wherein the geometry data connection (12), the ultrasound detector (1) and the combination device (5) are adapted to transfer geometry data additionally to the first image data from the ultrasound
- 20 detector (1) to the combination device (5) and wherein the geometry data comprise information for establishing a link between the geometry of the first image data and the geometry of the second image data.
2. The apparatus of claim 1, wherein the image data connection is adapted to
- 25 directly transfer the first image data in a digital format from the ultrasound detector (1) to the combination device (5).
3. The apparatus of claim 1 or 2, wherein the ultrasound detector (1) comprises a control unit (14) for controlling an image data generation of the ultrasound

MEDPT03027

13

11.04.03

detector (1) and wherein the control unit (14) is adapted to generate at least a part of the geometry data.

4. A method of combining first and second image data of an object (3), wherein
5 the first image data of the object (3) are repeatedly generated by an ultrasound
detector (1), wherein the second image data of the object (3) are generated
separately, for example the second image data have been recorded earlier by a
computer tomography, a magnetic resonance, a positron emission tomography
or an X-ray imaging device, wherein the first image data are transferred from
10 the ultrasound detector (1) to a combination device (5) and wherein the
combination device (5) is adapted to combine the first and second image data
of the object (3),
characterised by
transferring geometry data in addition to the first image data from the
15 ultrasound detector (1) to the combination device (5), wherein the geometry
data comprise information for establishing a link between the geometry of the
first image data and the geometry of the second image data.
5. The method of claim 4, wherein the geometry data comprise information
20 concerning at least one spatial dimension of an image unit of the first image
data, in particular of a pixel.
6. The method of claim 4 or 5, wherein the geometry data comprise information
concerning an image position of at least a part of an image, which is
25 represented by the first image data, relative to a reference point of the
ultrasound detector (1) or relative to a reference point or reference object in
the ultrasound image.
7. The method of one of claims 4 to 6, wherein the geometry data comprise
30 information concerning a detector position of the ultrasound detector (1)
relative to a position sensor (18) and/or relative to a signal source, for
determining a location and/or an orientation of the ultrasound detector (1).

MEDPT03027

14

11.04.03

8. The method of one of claims 4 to 7, wherein the geometry data comprise information concerning an orientation of the ultrasound image relative to a reference point or a reference object of the ultrasound detector (1).
- 5
9. The method of one of claims 4 to 8, wherein the geometry data are generated by and/or transferred from a control unit (14) of the ultrasound detector (1) and wherein the control unit (14) is adapted to control an image data generation of the ultrasound detector (1).
- 10
10. The method of one of claims 4 to 9, wherein the combination device (5) continuously displays a first image of the object (3) corresponding to the repeatedly generated first image data and continuously displays a second image of the object (3) corresponding to the second image data, wherein the orientation and/or scaling of at least a part of the object (3) is identical in the first and in the second image.
- 15
11. The method of one of claims 4 to 10, wherein at least a part of the geometry data is repeatedly transferred to the combination device (5), in particular every time when the first image data are generated.
- 20

1/3





Fig. 1

Fig. 2



2/3





Fig. 3

Fig. 4



3/3




Fig. 5

MEDPT03027

15

11.04.03

Applicants:

MedCom Gesellschaft für medizinische Bildverarbeitung mbH
Rundeturmstrasse 12, D-64283 Darmstadt, GERMANY and

Esaote S.p.A., via Ruffino Aliora, 32
15033 Casale Monferrato (AL), ITALY

Apparatus and Method for Combining First and Second Image Data of an Object

Abstract

The invention relates to a method of combining first and second image data of an object (3), wherein the first image data of the object (3) are repeatedly generated by an ultrasound detector (1), wherein the second image data of the object (3) are generated separately, for example the second image data have been recorded earlier by a computer tomography, a magnetic resonance or a positron emission tomography imaging device, wherein the first image data are transferred from the ultrasound detector (1) to a combination device (5) and wherein the combination device (5) is adapted to combine the first and second image data of the object (3).

Geometry data is transferred in addition to the first image data from the ultrasound detector (1) to the combination device (5), wherein the geometry data comprise information for establishing a link between the geometry of the first image data and the geometry of the second image data.

(Fig. 1)




Fig. 1

THIS PAGE BLANK (USPTO)